gutflix
GI learning, personalised

Summary

DEEP LEARNING FOR SEGMENTATION OF RECTAL CARCINOMAS WITH LINEAR ENDOSCOPIC ULTRASOUND

Jelmer Wolterink

UEG Week Copenhagen 2023 | Poster

Colorectal

October 15, 2023

A pilot study using convolutional neural networks to automatically segment endoscopic ultrasound images achieved 73% accuracy in distinguishing T1 from T2+ early rectal cancer, with 83% sensitivity for muscularis propria infiltration.

KEY POINTS

- The AI system was trained on 373 manually segmented EUS images from 80 patients and achieved a Dice similarity index of 0.82 for tumor segmentation, indicating good agreement with manual segmentation.
- For detection of muscular wall infiltration, the automated system achieved 83% sensitivity, 65% specificity, and 73% overall accuracy when tested against pathology.
- Clinical evaluation found useful segmentations in 81% of cases, though overtly misinterpreted images were excluded from clinical evaluation.
- The authors suggest these results from static images support further exploration of the approach, with expected improvement when applied to real-time dynamic EUS imaging.
- This work is relevant for endoscopists and gastroenterologists involved in staging early rectal cancer and making decisions about local versus radical resection.

VIEW THIS CONTENT ON GUTFLIX

https://gutflix.eu/search/d/7e727932-743b-11ee-a725-0242ac140004

AI-generated summary

This summary was generated by an AI large language model based on the content transcript. It is for informational purposes only and should not be considered a substitute for clinical judgment. Always rely on your professional expertise and the full clinical context when making clinical decisions.